



Optimizer-HF Specifications

General Specifications

Printer Dimensions:	Width:	65" (1651 mm)
	Length:	110" (2794 mm)
	Height:	50" (1270 mm)
Exit Height:		39" (990 mm)
Loading Height:		30" (762 mm) average over side guard
Weight:		1800 lbs. (817 kg)

Print Specifications

Print Area:	Width:	11" (280 mm); Option: 23" (584mm)
	Length:	32" (812 mm)
Resolution:		200 dots per inch (8 dots per millimeter)
Prints per Film:		5,000
Color:		Single color

Printer Capacities

Print Rate:	Variable:	Up to 60 cases per minute
Maximum Case Size:	Width:	42" (1067 mm)
	Length:	39" (990 mm)
	Thickness:	3/4" (20 mm)
Minimum Case Size:	Width:	10" (254 mm)
	Length:	12" (305 mm)
	Thickness:	1/16" (1.5mm)

Feed Table

Size:	Width:	30" (762 mm)
	Depth:	30" (762 mm)
Feed Direction		Operator side - right to left

Inking System

Type:	Continuous, with automatic level control
Pumps:	Dual peristaltic
Capacity:	2 gallons

Controls

Counter:	Batch
Control Panel Buttons:	Full set of control buttons
Overload:	Electronic overload protection in case of jam

Operating Requirements

Electric Power Supply:	240 VAC, single phase, 50-60 hz., 20 amps
Air Supply:	Minimum 80 psi clean shop air Consumption @ 30 cfm